

FINITURA UV R77

UV Lacquer based on special acrylic resins



Description

Single-component photoactivated product based on special acrylic resins, used as a finishing coat for matte effect for varnishing of wooden floors, furniture, doors and panels. It's characterized by excellent hardness, thermal expansion, uniformity and flexibility.

Characteristics

Preparation	photoactivated
Thinning (if necessary)	DILUENTE MONOMERICO
Application temperature	+10°C ÷ +25°C
Viscosity	40" - 50" Ford Cup 6
Application	single head roller coater / twin head roller coater / engraved roller
Coverage	7/15 g/m ²
Flash-Off	n.a.
Hardening	2/3 mercury lamps 80W cm ²
Gloss level	5 gloss
Dry residue	99%
Chemical and physical characteristics	excellent
Storage stability	1 year ⁽¹⁾
Packaging	25 KG
Machine cleaning	DILUENTE ACETONE

1 in original sealed containers at temperatures between +10°C and +25°C

How to use

Shake well before use.

FINITURA UV R77 is a UV finisher suitable for application by roller machine such as baby and roller laser. FINITURA UV R77 is generally applied on wooden floors previously treated with apposite primers. The regular and intense maintenance of wooden floors treated with FINITURA UV R77 should be made with the VELUREX products line (see technical data sheet).

Label elements

· For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.