

FONDO FOW R700

Single-component, fast-drying water bottom for wood floor roller coater application



Description

FONDO FOW R700 is a single-component polyurethane water primer for roller applications, specific for the first coat of parquet and wood painting cycles in general. FONDO FOW R700 has high dry residue, fast drying, easy sanding. In addition, it gives the wood a warm tone, especially on oak wood, as well as a pleasant aesthetic appearance.

Characteristics

Mixture ratio	single-component
Application temperature	+10°C ÷ +25°C
Application	roller coater
Thinning (if necessary)	DILUENTE DR H20
Coverage	30-50 g/m ²
Dust dry	20' ⁽¹⁾
Fingerprint dry	40' ⁽¹⁾
Sanding	12 h ⁽¹⁾
Wood oxidation	low
Pore filling	good
Storage stability	1 year ⁽²⁾
Packaging	25 Kg
Tool cleaning	DILUENTE DNH 40 (with fresh product)

1 at 20°C and 65% R.H.

2 in original sealed containers at temperatures between +10°C and +25°C

How to use

Shake well before use.

FONDO FOW R700 is a high viscosity primer for general use, suitable for roller applications. FONDO FOW R700 is applied on a wooden floor previously stuccoed, sanded with 120-150 paper and carefully vacuumed. After drying and sanding apply our single/two-component water lacquer or our FINITURA UW R800 (see the relevant data sheet).

Notes:

The sanding of FONDO FOW R700 must be carried out in a uniform way to avoid uneven color variations.

Label elements

· For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.