

Technical Datasheet

Item Code: - | Rev.: 15-09-2023 | Ver: 3.3

SERIE VSC

Chimiver solvent-borne mediums for dyes



Description

The VSC series contains all the solvent-borne mediums to be used in the preparation of dyes for wood. Depending on the type of application and the characteristics required, you can choose between different types of mediums.

Characteristics

Appearance	liquid / viscous liquid
Application	brush, rag, spray, roller
Application temperature	10°C - 25°C
Thinning (if necessary)	DLC-0044; DLC-0022; DMC-0070; DNS-0018; DMC-0029
Storage stability	1 year ⁽¹⁾
Packaging	1 L - 5 L - 10 L

1 in original sealed containers at temperatures between +10°C and +25°C

Available Versions

VSC-0010: Medium viscosity medium for general purpose, specific for spray, spray/rag and sponge roller applications. Medium drying speed.

VSC-0011: High viscosity medium specific for dyes applied with rubber roller. Used in mixture with VSC-0010 to change the viscosity. Quick drying.

VSC-0015: Medium for spray applications where excellent colour uniformity and low pore marking are required.

Label elements



For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a practical test by the user who assumes the full responsibility of the final result of his work.